



GREENBRIDGE

PNEUMATIC TENSIONER & SEALER FOR STEEL

THE SP3100 + SP6000 SERIES

Unlock the potential of efficiency and convenience with our **SP6000 Series** Pneumatic Steel Strapping Sealers and the **SP3100** Steel Strap Tensioner!

Designed to be light weight and compact, Greenbridge sealers effortlessly produce efficient single notch joints, ensuring a secure finish to your packaging. When paired with the SP3100 series strap tensioner, you'll experience a seamless and swift strapping process for both flat and round surface packages.

No more cumbersome strapping struggles - our system offers a quick and easy solution that saves you time and effort. Compatible with steel strap sizes ranging from 3/4" to 1 1/4", our solution adapts to your diverse packaging needs, providing versatility and reliability with every use.

Elevate your steel banding efficiency and reliability with our SP6000 Series Pneumatic Steel Strapping Sealers and SP3100 Steel Tensioner today!



SP3100 Tensioner

Discover the swift and effortless solution for strapping flat and round surface packages with our SP3100 series pusher bar strap tensioner, compatible with strap sizes from 3/4" to 1 1/4". Combine seamlessly with the SP6100 series strap sealers for a streamlined packaging process.

Inclined SP3100 available!



SP6000 Series Sealers

Greenbridge's steel strapping power tools are ergonomically designed, easy to use, and durable. SP series offers both seal and non seal models for fast and efficient tensioning and closure. With several models to choose from, there is a system for almost every application.

24/7 INSTANT
ACCESS TO MANUALS



SCAN ME

VIA SMART PHONE!

LET'S GET DOWN TO BUSINESS.

SP3100 + SP6000 SERIES SPECS



SPECIFICATIONS

	SP3100	SP6119	SP6125	SP6132
Length	13.5"	12.6"	12.6"	12.6"
Width	4.5"	5.5"	5.5"	5.5"
Height	3.5"	7"	7"	7"
Weight	9.5 lbs	6.5 lbs	6.5 lbs	6.5 lbs
Strap Size	3/4", 1", 1 1/4"	3/4"	1"	1 1/4"
Thickness	.024" - .043"	RD .024 - .039 HT .025 - .031	RD .024 - .039 HT .025 - .031	RD .024 - .039 HT .025 - .031
Pressure Consumption	14L/s-29 cu ft/mi	14L/s-29 cu ft/mi	14L/s-29 cu ft/mi	14L/s-29 cu ft/mi
Pressure Range	5.5 - 7bar / 77-99 psi			
Seal		Various	Various	Various
Max Tension	3300 lbs			
Tension Speed	6m/min			
Type		Push	Push	Push
Notch		Single Reverse	Single Reverse	Single Reverse

AIR SUPPLY



There are TWO important functions, pressure and volume. Without the proper volume as well as pressure, the tool will not perform or function properly. The air line should be constructed according to this diagram and drained daily.

Service Is Everything

Tool not working as it should?

Contact Greenbridge.

We service your tool and get it backup and running.

Ask about our steel tool service program!

ABOUT GREENBRIDGE

Founded in 1974 as Polychem, we rebranded in April 2021 as Greenbridge to reflect our commitment to providing proactive solutions to customers across North America seeking to achieve more sustainable, high-performing operations. Our early reputation was based on our quality polyester, polypropylene and cord strapping. Today, years of growth and strategic acquisitions have made Greenbridge a leading end-of-line packaging supplier, with integrated solutions that encompass tools, equipment, systems, and services that help tame the most challenging supply chains.

Greenbridge is committed to the safety of our team, the quality of our products and services, investing in continuous improvement, advancing the circular economy, and fostering sustainable customer success.



03/24

