# G GREENBRIDGE

# **SOLUTIONS FOR BUNDLING**

# N3400A AUTOMATIC STRAPPING MACHINE

Introducing the N3400A arch machine - Your Ultimate Solution for Efficient Strapping! Enjoy uninterrupted performance with 55 cycles per minute, ensuring rapid and precise strapping for various applications, including boxes, lumber, and print media. The N3400A has been upgraded with a wear-free strap frame featuring stainless steel guides and an operation terminal equipped with soft buttons, making it intuitive and easy to operate. Bid farewell to manual hassles as the automatic start feature streamlines your strapping process. This innovative solution ensures not only hassle-free operation but also durability, making the N3400A the go-to choice for efficient and reliable strapping applications. Moreover, the N3400A requires less maintenance with its brushless direct drive motors, providing a cost-effective and user-friendly strapping solution.

# The N3400A is Ideal for



**Pharmaceuticals** 



**Graphic Arts** 



Distribution



Meat Processing (Stainless Steel)

# ENERGY SAVING MOTORS!



## **FEATURES**

- Up to 35 cycles per minute, depending on tension settings and package size
- Wear-free, Energy Saving direct-drive motors
- Wear-free strap frame with stainless steel guides
- ASLF 'Anti-Strap-Loss-Function' constant strap control

- DAT 'Direct Access Technology'
- Automatic strap feed
- Strap width 5-12 mm
- Upstream and downstream interlocks
- Exclusive eject function avoids strap jam
- Conveyor speed steplessly adjustable
- Intuitive operator interface

- Machine Movable
- MFT 'Mono-Frame-Technology'
- Bundle press, optional
- Table height steplessly adjustable
- SAO 'Safe and Open' Safe without protection doors
- Bundle flow control



# INNOVATIVE, RELIABLE, ENERGY-SAVING

N3400A EQUIPMENT SPECS



## **SPECIFICATIONS**

Cycle Rate	Up to 35 cycles per minute
Cycle Initiation	Photo eye sensor
Package Weight	639 lbs. (290kg)*
Package Size	Min. 1.5" H x 3" W (Max. Governed by Arch)
Strap Tension	Adjustable Electronic Control
Strap Size	5mm-12mm
Standard Arch Size	600mm(W) x 600mm(H)
Seal Head Location	Bottom
Sealing Method	Heat Seal
Mobility	3" Casters
Dispenser	Externally Located
	8" or 9" I.D./ 8" Face/ 18" O.D.
Power	120V Single Phase



**All Metal Strap Drive Rollers** 



**HOT Knife Sealing Technology** 



DAT (Direct Access Technology)



Fewer Moving Wear Parts

#### **ADDITIONAL OPTIONS:**

Power Roller Table Tops, Press Bar, 220V 1PH or 480V 3PH Power, Additional arch sizes available

## ABOUT GREENBRIDGE

Founded in 1974 as Polychem, we rebranded in April 2021 as Greenbridge to reflect our commitment to providing proactive solutions to customers across North America seeking to achieve more sustainable, high-performing operations. Our early reputation was based on our quality polyester, polypropylene and cord strapping. Today, years of growth and strategic acquisitions have made Greenbridge a leading end-of-line packaging supplier, with integrated solutions that encompass tools, equipment, systems, and services that help tame the most challenging supply chains.

Greenbridge is committed to the safety of our team, the quality of our products and services, investing in continuous improvement, advancing the circular economy, and fostering sustainable customer success.

It's easy to find a supplier to sell you equipment.

It's another thing to find one who understands your business.

Talk to Greenbridge.

