

STEEL STRAPPING TOOL > PNEUMATIC

Pneumatic Steel Strapping Tool with Seal - UPCUT Joint for 19mm / 25mm / 32mm Steel Strap



SP5200 is the combined double notch UP-CUT seal joint pneumatic strapping tool, studied for 19mm / 25mm / 32mm steel straps.

This tool is equipped with 2 operating buttons, to allow an Automatic tension of Your steel strap.

SP5200 is available in two motor versions (9000 N and 15000 N) to provide the most suitable and adjustable tension for Your application.

Easy to be used, SP5200 is already equipped with its suspension hook to grant a lighter operation mode to arrange a perfect double notch seal joint.

Powerful, quick and strong, SP5200 is manufactured to be durable and with very low maintenance required.

FEATURES

- 2 Operating Buttons
- Strong and Reliable
- Easy to be used
- Low Maintenance Required
- Powerful and Quick

BENEFITS

- Double Notch UP-CUT Seal Joint
- Automatic Tension
- Robust and durable
- For a wide range of steel Straps
- Suspension hook already equipped

TECHNICAL SPECIFICATION

Dimensions	430 x 260 x 310 mm
Weight	11,3 Kg

STRAP

Type	Steel Strap - regular & high tensile
Width	19mm / 25mm / 32mm
Thickness	0,6mm - 1,0mm (Regular duty) 0,63mm - 0,8mm (High Tensile)

POWER SUPPLY

Pressure Range	5,5 - 7 bar (87 - 99 psi)
Air Consumption	12 L/s - 25 cuft/min

PERFORMANCE

Max. tension force	9000N - 15000N (6 bar - 87 psi)
Tensioning Speed	3,8 mt/min @9000N 5,2 mt/min @15000N
Sealing	Seal Double Notch
Joint Strenght	75% of breaking strenght*

* variable according to strap type

MODEL

CODE	DESCRIPTION
ET529M	19mm Steel - 9000N
ET523M	25mm Steel - 15000N

A  **GREENBRIDGE BRAND**

 **ITATOOLS**[®]
PLASTIC & STEEL STRAPPING TOOLS